Crow Cams Australia Pty Ltd
1 Griffith Street, Knoxfield VIC 3180
Tel: 03 9357 0469 Email: info@crowcams.com.au

CAMSHAFT SPECIFICATIONS

Part number: 871285C **Cam Type:** Hydraulic roller

Adv ground on Cam:	2°	LSA:	108°	ICL:	106°
Inlet Lobe lift at TDC:	.086"			ECL:	110°

Valve Timing	In opens:	12 BTDC	Ex opens:	49 BBDC	Duration:	235°
@ .050"	In closes:	43 ABDC	Ex closes:	9 ATDC	Duration:	238°
Adv Valve Timing	In opens:	39 BTDC	Ex opens:	76 BBDC	Duration:	293°
@ .006"	In closes:	74 ABDC	Ex closes:	38 ATDC	Duration:	295°

In Lobe Lift (inch)	0.350	Ex Lobe Lift:	0.349	Rocker Ratio:	1.7
In Valve lift (inch)	0.595	Ex Valve lift:	0.594		

These high performance components should be checked for suitability by the person installing them as engines of the same group can vary in valve length, spring installed height and collet grooves.
IT IS THE SOLE RESPONSIBILITY OF THE INSTALLER TO CHECK SUITABILITY.